




## CLASS 150 SLIP-ON

### ASME B16.47 SERIES A

These Slip-on are not covered by B16.47, the list here have been added for completeness



1	2	3	4	5	6	7	8	9	10	11
BOLT										
Nominal Pipe Size	Outside Diameter <i>O</i>	Min. Thickness <i>t<sub>r</sub></i>	Diameter of Raised Face <i>R</i>	Diameter of Hub <i>X</i>	Length Through Hub <i>Y1</i>	Bore <i>B1</i>	Minimum Fillet Radius	Bolt Circle Dia	Number of Holes	Diameter of Holes
26	34.25	2.69	29.50	28.25	3.69	26.25	0.38	31.75	24	1.38
28	36.50	3.06	31.50	30.50	3.81	28.25	0.44	34.00	28	1.38
30	38.75	3.31	33.75	32.50	3.94	30.25	0.44	36.00	28	1.38
32	41.75	3.41	36.00	34.50	4.18	32.25	0.44	38.50	28	1.62
34	43.75	3.68	38.00	36.50	4.25	34.25	0.50	40.50	32	1.62
36	46.00	3.96	40.25	38.75	4.56	36.25	0.50	42.75	32	1.62
38	48.75	4.06	42.25	41.25	4.56	38.25	0.50	45.25	32	1.62
40	50.75	4.18	44.25	43.25	4.81	40.25	0.50	47.25	36	1.62
42	53.00	4.43	47.00	45.50	5.06	42.25	0.50	49.50	36	1.62
44	55.25	4.68	49.00	47.75	5.18	44.25	0.50	51.75	40	1.62
46	57.25	4.86	51.00	49.75	5.31	46.25	0.50	53.75	40	1.62
48	59.50	5.06	53.50	52.00	5.56	48.25	0.50	56.00	44	1.62
Notes:										
(1) This dimension is for the large end of the hub, which may be straight or tapered. Taper shall not exceed 7 deg on threaded, slip-on .										
(2) When these flanges are required with flat face, the flat face may be either the full <i>t<sub>r</sub></i> dimension thickness plus 0.06 in. or the <i>t<sub>r</sub></i> dimension thickness without the raised face height.										